

Description

Background

[0001] This invention relates to a bearing assembly and method for a rotating member, and, more particularly, to a bearing assembly and method involving a bearing cage that extends between the rotating member and a bearing housing.

[0002] In many bearing designs of the above type, it is necessary to have a fairly precise engagement between the bearing cage and the bearing housing that will be sufficient through the range of manufacturing clearances of the bearing housing and bearing cage, yet will not generate a too high clamping force to deform the housing and cage, thereby maintaining a positive seal at the joint between the housing and cage, and improving control of the bearing geometry.

Summary

[0003] According to an embodiment of this invention, a bearing cage extends between a rotating member and a bearing housing and engages the housing in a manner to insure that the engagement is sufficient through a range of manufacturing clearances of each component, yet does not generate too high a clamping force to deform the housing and cage, thereby maintaining a positive seal at the joint between the housing and cage, and improving control of the bearing geometry.

Brief Description of the Drawings

[0004]

Fig. 1 is a cross-sectional view of the bearing assembly according to an embodiment of the present invention, shown in operative engagement with a rotor, which is shown in elevation.

Fig. 2 is an enlarged cross-sectional view of a portion of the bearing assembly of Fig. 1.

Detailed Description

[0005] Referring to Fig. 1 of the drawings, the reference numeral 10 refers in general to the bearing assembly according to an embodiment of the invention which surrounds a rotor 12. It is understood that the rotor 12 is rotated about its axis and forms part of an assembly that includes a driving system for imparting torque to the rotor, in a conventional manner.

[0006] An annular bearing cage 16 extends around the rotor 12 and has a internal recess formed therein for receiving a series of tilt pads 18, one of which is shown, which form the bearing members. Since the tilt pads 18 are conventional they will not be described in detail. It is also understood that one or more of the cage 16, and the housing 20 can be formed by two split arcuate sec-

tions that are attached at their respective ends, in a conventional manner.

[0007] A plurality of angularly-spaced, axially-extending, grooves, two of which are referred to by the reference numerals 16a and 16b, are formed in the outer periphery of the cage 16. The grooves 16a and 16b are spaced radially inwardly from the outer radial surface of the cage 16 a predetermined amount to form cantilevered portions 16c and 16d that extend radially outwardly from the respective grooves. The thickness of each cantilevered portion 16c and 16d is such that it functions as a mechanical spring in a manner to be described.

[0008] A radially-extending passage 16e is formed through the cage 16 for supplying lubricating oil to the tilt pad 18, in a manner to be explained.

[0009] An annular housing 20 surrounds the cage 16 and has an internal annular recess 20a which communicates with a radially-extending through passage 20b. Oil can thus be introduced to the passage 20b and passes through the latter passage, the recess 20a and the passage 16e of the cage 16 for supplying oil to the tilt pads 18.

[0010] A majority of the radial inner surface of the housing 20 is slightly spaced from the radial outer surface of the cage 16, including the cantilevered portions 16c and 16d, to form an annular clearance C which communicates with the recess 20a of the housing 20 and thus receives some of the above-mentioned oil.

[0011] The respective axial end portions of the radial outer surface of the cantilevered portions 16c and 16d are enlarged so as to project radially outwardly from the plane of the latter portions and engage the corresponding inner surfaces of the housing 20 in an interference fit. The enlarged portion associated with the cage portion 16c is shown by the reference 16f in Fig. 2. These enlarged portions, including the portion 16f, prevent the leakage of oil from the clearance C; and the axial lengths of the raised portions, including the portion 16f, are designed to minimize contact stresses between the cage 16 and the housing 20.

[0012] The thickness of each cage portion 16c and 16d is such that the stiffness of the mechanical springs formed by each portion can be adjusted relative to the bearing stiffness of the tilt pads 18.

[0013] The system 10 of the above embodiment thus has the following advantages:

1. A relatively low clamping force acts on the bearing housing 20 to eliminate the risk of deformation and leakage.
2. No deformation of the inside of the cage 16 occurs where the tilt pads 18 contacts the cage, allowing a much better control of the tilt pad bearing geometry.
3. There is less sensitivity to temperature effects on the housing 20 resulting in minimum deleterious effects on the interference fit between the enlarged portions, including portion 16f, of the cantilevered

portions 16c and 16d and the corresponding surfaces of the housing 20.

4. The presence of the oil in the clearance C provides additional damping of the bearing assembly 10 in general, thus significantly increasing the damping provided to the rotor 12.

[0014] It is understood that variations may be made in the foregoing without departing from the scope of the invention. For example, the number of angularly-spaced grooves formed in the cage 16 can vary and, in fact there can be only one groove that is continuous in an angular direction. Also, the radial and axial lengths of the cage portions 16c and 16d, including the enlarged portion 16f, can vary from those shown in the drawings. Also the sealing between the bearing housing and cage can be done by other means than metal to metal contact as shown on the drawings.

[0015] Since other modifications, changes, and substitutions are intended in the foregoing disclosure, it is appropriate that the appended claims be construed broadly and in a manner consistent with the scope of the invention.

Claims

1. A bearing assembly for a rotor, the assembly comprising a cage surrounding the rotor, and a housing surrounding the cage, a first portion of the radial outer surface of the cage extending in a slightly spaced relation to the corresponding portion of the inner surface of the housing, and a second portion of the radial outer surface of the cage projecting from the first portion in a radial direction and engaging the corresponding portion of the inner surface of the housing.
2. The assembly of claim 1, wherein the cage and the housing are annular.
3. The assembly of claim 1 or 2, wherein at least one axially-extending groove is formed in the cage to form a cantilevered portion extending between the groove and the corresponding outer radial surface of the cage.
4. The assembly of claim 3, wherein the cantilevered portion forms a mechanical spring.
5. The assembly of any one of the preceding claims, wherein a plurality of grooves are formed in the cage and extend in an angularly-spaced relationship to form a plurality of cantilevered portions, respectively.
6. The assembly of claim 5, wherein each of the cantilevered portions forms a mechanical spring.
7. The assembly of any one of claims 1 to 4, wherein there is one continuous annular groove.
8. The assembly of any one of the preceding claims, wherein a clearance is formed between the first portion of the radial outer surface of the cage and the corresponding portion of the inner surface of the housing for introducing oil to the clearance.
9. The assembly of claim 8 further comprising a recess formed in the cage and a passage extending through the cage and to the recess, the latter passage receiving the oil from the clearance and passing it to the recess, and further comprising tilt pads disposed in the recess.
10. The assembly of any one of the preceding claims, wherein the second portion of the radial outer surface of the cage is disposed at the respective axial end portions of the cage.
11. A method of positioning a bearing cage and a bearing housing around a rotating member, the method comprising disposing the cage around the rotor, and disposing the housing around the cage, with a first portion of the radial outer surface of the cage extending in a slightly spaced relation to the corresponding portion of the inner surface of the housing, and with a second portion of the radial outer surface of the cage projecting from the first portion in a radial direction and engaging the corresponding portion of the inner surface of the housing.
12. The method of claim 11, wherein the cage and the housing are annular.
13. The method of claim 11 or 12, further comprising forming at least one axially-extending groove in the cage to form a cantilevered portion extending between the groove and the corresponding outer radial surface of the cage.
14. The method of claim 13, wherein the cantilevered portion forms a mechanical spring.
15. The method of any one of claims 11 to 14, wherein a plurality of grooves are formed in the cage and extend in an angularly-spaced relationship to form a plurality of cantilevered portions, respectively.
16. The method of claim 11 or 12, wherein there is one continuous annular groove.
17. The method of any one of claims 11 to 16, wherein a clearance is formed between the first portion of the radial outer surface of the cage and the corresponding portion of the inner surface of the housing, and further comprising a passage formed in the

housing for introducing oil to the clearance.

18. The method of claim 17, further comprising forming a recess formed in the cage and forming a passage extending through the cage and to the recess, the latter passage receiving the oil from the clearance and passing it to the recess, and further comprising providing a tilt pad in the recess. 5
19. The method of claim 17 or 18, wherein the second portion of the radial outer surface of the cage is disposed at the respective axial end portions of the cage to prevent the leakage of oil from the clearance. 10
20. The method of any one of claims 11 to 19, wherein the second portion of the radial outer surface of the cage is disposed at the respective axial end portions of the cage. 15
- 20
- 25
- 30
- 35
- 40
- 45
- 50
- 55



(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
04.08.2004 Bulletin 2004/32

(51) Int Cl.⁷: **F16C 17/03**, F16C 27/02,
F16C 27/04, F16F 15/023

(43) Date of publication A2:
09.04.2003 Bulletin 2003/15

(21) Application number: 02022237.8

(22) Date of filing: 02.10.2002

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
IE IT LI LU MC NL PT SE SK TR
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 03.10.2001 US 970319

**(71) Applicant: Dresser-Rand Company
Olean, NY 14760 (US)**

(72) Inventors:


- Dourlens, Herve H.
76290 Manne-villette (FR)
- Marshall, Dale F.
76600 Le Havre (FR)
- Auber, Philippe
76620 Le Havre (FR)

(74) Representative: **HOFFMANN - EITLE**
Patent- und Rechtsanwälte
Arabellastrasse 4
81925 München (DE)

(54) Bearing assembly and method

(57) A bearing assembly and method in which a bearing cage is disposed around a rotating member and a housing is disposed around the cage. A first portion of the radial outer surface of the cage extends in a slightly

spaced relation to the corresponding portion of the inner surface of the housing, and a second portion of the radial outer surface of the cage projects from the first portion in a radial direction and engages the corresponding portion of the inner surface of the housing.





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 02 2237

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 215 385 A (IDE RUSSELL D) 1 June 1993 (1993-06-01) * column 9, line 36 - column 12, line 39 * * figures 1,3A,3B,4A-4C * ---	1-4,7, 10-14, 16,19,20	F16C17/03 F16C27/02 F16C27/04 F16F15/023
X	US 4 027 931 A (STREIFERT KEITH L) 7 June 1977 (1977-06-07) * the whole document * ---	1,2, 8-12, 17-20	
X A	DE 28 47 979 A (BOSCH GMBH ROBERT) 22 May 1980 (1980-05-22) * the whole document * ---	1,2,11, 12 5,6,15	
A	US 5 425 584 A (IDE RUSSELL D) 20 June 1995 (1995-06-20) * the whole document * ---	1-20	
A	US 4 134 309 A (BALKE RODNEY W ET AL) 16 January 1979 (1979-01-16) * the whole document * -----	1-4, 11-14	TECHNICAL FIELDS SEARCHED (Int.Cl.7) F16C F16F
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 7 June 2004	Examiner Prieto Sanz, M.D.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document	

EPO FORM 1503 03/02 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 02 2237

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

07-06-2004

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5215385 A	01-06-1993	US 5013947 A	07-05-1991
		US 5142174 A	25-08-1992
		AU 648719 B2	28-04-1994
		AU 7570991 A	10-10-1991
		CA 2081375 A1	17-09-1991
		CN 1056193 A	13-11-1991
		EP 0520019 A1	30-12-1992
		IE 910696 A1	25-09-1991
		JP 5505721 T	19-08-1993
		PT 97048 A	31-03-1993
		WO 9114308 A1	19-09-1991
		ZA 9101934 A	24-12-1991
US 4027931 A	07-06-1977	BR 7606554 A	05-07-1977
		CA 1050597 A1	13-03-1979
		CH 612250 A5	13-07-1979
		DE 2644026 A1	14-04-1977
		DK 442276 A	04-04-1977
		FR 2326615 A1	29-04-1977
		GB 1530648 A	01-11-1978
		IT 1074026 B	17-04-1985
		JP 52145653 A	03-12-1977
		MX 144922 A	04-12-1981
		NL 7610874 A ,B,	05-04-1977
		NO 763363 A ,B,	05-04-1977
DE 2847979 A	22-05-1980	DE 2847979 A1	22-05-1980
US 5425584 A	20-06-1995	US 5137373 A	11-08-1992
		US 5112143 A	12-05-1992
		AT 160620 T	15-12-1997
		AU 4119293 A	29-11-1993
		BR 9306276 A	30-06-1998
		CA 2134114 A1	11-11-1993
		DE 69315430 D1	08-01-1998
		DE 69315430 T2	25-06-1998
		EP 0637361 A1	08-02-1995
		JP 7505945 T	29-06-1995
		NO 943934 A	20-12-1994
		US 5421655 A	06-06-1995
		WO 9322575 A1	11-11-1993
		US 5531522 A	02-07-1996
		US 5603574 A	18-02-1997
		ZA 9302866 A	08-09-1994
		AT 124507 T	15-07-1995
		AU 609992 B2	09-05-1991

EPO FORM P459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 02 2237

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

07-06-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5425584	A		AU 3521389 A	30-11-1989
			BR 8904390 A	05-03-1991
			CA 1337663 C	28-11-1995
			CN 1038145 A ,B	20-12-1989
			DE 68923221 D1	03-08-1995
			DE 68923221 T2	16-11-1995
			DK 257189 A	28-11-1989
			EP 0343620 A2	29-11-1989
			EP 0646746 A2	05-04-1995
			ES 2074452 T3	16-09-1995
			FI 892584 A	28-11-1989
			GR 3017155 T3	30-11-1995
			IE 72194 B1	26-03-1997
			IL 90234 A	21-02-1993
			JP 2076924 A	16-03-1990
			JP 2745067 B2	28-04-1998
			KR 9311369 B1	04-12-1993
			MX 171668 B	10-11-1993
			NO 892141 A ,B,	28-11-1989
			PT 90671 A ,B	30-11-1989
			US 5372431 A	13-12-1994
			US 5382097 A	17-01-1995
			US 5743654 A	28-04-1998
			US 5393145 A	28-02-1995
			US 5660481 A	26-08-1997
			US 5558444 A	24-09-1996
			US 5503479 A	02-04-1996
			US 5403154 A	04-04-1995
			US 5564836 A	15-10-1996
			US 5459674 A	17-10-1995
			US 5620260 A	15-04-1997
			US 5556208 A	17-09-1996

US 4134309	A	16-01-1979	NONE	

EPO FORM P0499

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

